

CTEK PRO25S/PRO25SE

VERSATILE POWER SUPPLY AND CHARGER FOR WORKSHOP SUPPORT



CTEK PRO25S/PRO25SE

VERSATILE POWER SUPPLY AND CHARGER FOR WORKSHOP SUPPORT

PRO25S and PRO25SE are tough, powerful battery support tools for everyday servicing and diagnostic work. They're ideal for technicians' personal use to complement workshop programming equipment perfectly.

Easy to use and fully automatic, with temperature compensation for ambient conditions between -20°C and +50°C (-4°F to +122°F). Both PRO25S and PRO25SE are suitable for all types of 12V battery, including lithium iron phosphate.



WHY YOU NEED CTEK BATTERY SUPPORT

Battery support is an essential tool for all types of diagnostic, service and repair work in the professional workshop. CTEK's PRO25S and PRO25SE give you powerful 12V supply, charging and maintenance programs in versatile, highly efficient units that will help save you valuable time and money.

Like all CTEK PRO Series products, PRO25S and PRO25SE have automatic parallel load compensation which makes sure that power supply voltage and amperage are always constant and correct, even if the battery has an additional load placed on it during diagnostic work.





KEY PRODUCT FEATURES

- Up to 25A of battery support
- 12V power supply support for code reading, electrical circuit testing and fault finding
- Fast, fully automatic 8-step charging
- 'NORMAL' program for 12V lead-acid, WET, Ca/Ca, AGM, MF and GEL batteries
- Also suitable for lithium iron phosphate batteries
- 'RECOND' mode to recondition deeply discharged lead-acid batteries
- Automatic temperature compensation
- PRO25S comes with 2m charging cables
- PRO25SE comes with 6m charging cables and wall hanger

TECHNICAL INFORMATION

| Power supply | Max 25A, 13.6V |
|-------------------------------|--|
| Charging voltage | Lead acid: 14.4V/15.8V/13.6V, Lithium: 13.8V/14.4V/13.3V |
| Battery types | 12V Lead acid: Wet, Ca/Ca, AGM, EFB (Start/Stop types) and Gel 12V Lithium: LiFePO4 |
| Battery capacity | Lead acid: 40-500Ah, Lithium: 30-450Ah |
| Start voltage | 2V start up voltage for charging |
| Parallel load compensation | Automatic |
| Ripple | Less than 4% |
| Ambient operating temperature | -20°C to +50°C (-4°F to +122°F) |
| Degree of protection | IP44 |
| Mains cable length | 1.9m (AC cable) |
| Charge cable length | PRO25S: 2m, 6mm² (DC cable) PRO25SE: 6m, 6mm² (DC cable) |
| Net weight (unit with cables) | PRO25S: 1.8kg, PRO25SE: 3.2kg |
| Warranty | 2 years |

SUITABLE ACCESSORIES

BUMPER 300

Durable rugged protection for your charger with a convenient carry handle.



wall or ramp posts.

WALL HANGER 300

Specially designed to enable the

charger to be mounted onto the



TROLLEY PRO

Carry all of your test equipment with this custom designed, heavy duty trolley.







WHY CHOOSE CTEK?

CTEK invented the smart charger over 25 years ago and is now the leading global brand in vehicle battery support, care and maintenance.

Our professional range of battery support equipment and chargers is high quality, tough and reliable, and used in a wide variety of applications, from professional workshops and showrooms to domestic use.

We also produce branded chargers for over 50 of the world's biggest and most prestigious car manufacturers.

We offer the ultimate in battery support and charging for all types of vehicle. Packed with new and unique features, our extensive range of products maximises battery performance and delivers the complete vehicle and battery support solution.

