



THE ULTIMATE CTEK BATTERY CARE KIT!

This limited edition all-in-one kit includes everything you need for optimal battery care.

CT5 TIME TO GO

The CT5 TIME TO GO is the first charger in the world to tell you exactly when your battery will be charged and ready to go. A series of LED lights indicate the different charging stages, and how long (in hours) your battery has to go before it's charged.

The CT5 TIME TO GO uses advanced technology to give you three charging and maintenance programs – Normal, AGM and Recond. It's easy to use and fully automatic, so it can be connected directly to the battery indefinitely, if required, and it won't over or under charge.

- Countdown Timer and Start Indicator
- Built-In Temperature Compensation
- AGM & Reconditioning Mode
- Connect and Forget



INDICATOR EYELET M8

The CTEK INDICATOR EYELET M8 connector is ideal for charging and checking batteries that are difficult to get to or hidden. The LED 'traffic light' system shows your battery's charge status simply and clearly. Connect the eyelet terminals to the battery, check the status, then plug the connector into your CTEK charger if the battery needs charging.



CONNECT CLAMP

The CTEK CONNECT CLAMP gives you a quick and easy way to connect your CTEK charger using CTEK's unique CONNECT system. These tough, durable and flexible clamps ensure you have a secure, safe and snug connection to your battery.

CT5 TIME TO GO BATTERY CHARGER KIT



BUMPER 60

The CTEK BUMPER fits snugly round the body of your CTEK charger to protect it from bumps and scratches. Made from durable silicon rubber, the BUMPER gives your charger extra grip on slippery surfaces.



CS STORAGE CASE

Keep your battery charger with you wherever you go in this practical, lightweight padded bag.

TECHNICAL DATA

INPUT	220-240 VAC, 50-60 Hz, 0.6 A
OUTPUT	14.4/14.7/15.8 V, 5.0 A
BATTERY TYPES	12 V: WET, MF, Ca/Ca, AGM, GEL
BATTERY CAPACITY	20-160 Ah
START VOLTAGE	2.0 V
BACK CURRENT DRAIN*	Corresponding to less than 1.5 Ah/month
BATTERY VOLTAGE	12 V
AMBIENT OPERATING TEMPERATURE	-20 °C to +50 °C
TEMPERATURE COMPENSATION	Built-in compensation of charging voltage based on ambient temperature.
BATTERY CHEMISTRY	Lead acid
DEGREE OF PROTECTION	IP65
WARRANTY	5 years

*) Back current drain is the current that drains the battery if the charger is not connected to the mains. CTEK chargers have a very low back current.

GUARANTEED QUALITY WITH CTEK

CTEK customer support is available to answer any questions related to charging and CTEK chargers. Safety, simplicity and flexibility characterizes all products and solutions developed and sold by CTEK. CTEK supply chargers to more than 70 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious car and motorcycle manufacturers.

For more information visit WWW.CTEK.COM